

NR-H1200DF Dual Fuel Boiler

NR-H1200DF

Product Overview

Versatile – condensing boilers suitable for use with either diesel or gas burners
– for use within a wide range of different applications

Weatherproof – installed within a steel frame suitable for external siting

Fully packaged – complete with all necessary safety valves/switches along with flexible connections to ease installation

Wide range of ancillaries available – fuel tanks, fuel lines, calorifiers, hoses & cables can all be supplied to provide a complete solution



Performance Data

Nominal Heating Capacity.....1,200 kW
Nominal Fuel Consumption – Diesel130 l/hr
Nominal Fuel Consumption – Gas135 m³/hr

Operating Limits

Minimum/Maximum Heating Fluid Supply Temperature 50/90 °C
Maximum Working Pressure 5.0 bar

Electrical Data

Power Supply400/3/50 V/ph/Hz
Power Connection 32 A 5 Pin Plug

Hydraulic Circuit

Nominal Heating Fluid Flow Rate68 m³/hr
Connections 100 mm
Expansion Tank Volume 500 litres

Physical Data

Length6,096 mm
Width2,439 mm
Height2,621 mm
Operating Weight.....9,000 kg

Still have a question?

Get in touch with one of our expert team today.

☎ 01422 371711
✉ sales@newsome.ltd.uk
🌐 www.newsome.ltd.uk

