

# NR-H300G Gas Boiler

NR-H300DF

## Product Overview

- Compact** – very small footprint provides site flexibility
- Weatherproof** – installed within a steel frame suitable for external siting
- Added redundancy** – consists of 2 x 150 kW gas fired boilers to provide extra peace of mind
- Fully packaged** – complete with all necessary safety valves/switches along with flexible connections to ease installation
- Suitable for single phase supply** – large heating capacity is achieved from a relatively small electrical load
- Wide range of ancillaries available** – fuel tanks, fuel lines, calorifiers, hoses & cables can all be supplied to provide a complete solution



## Performance Data

Nominal Heating Capacity.....300 kW  
Nominal Fuel Consumption – Gas .....34 m<sup>3</sup>/hr

### Operating Limits

Minimum/Maximum Heating Fluid Supply Temperature ..... 50/90 °C  
Maximum Working Pressure .....10.0 bar

### Electrical Data

Power Supply .....230/1/50 V/ph/Hz  
Power Connection .....16 A 3 Pin Plug

### Hydraulic Circuit

Nominal Heating Fluid Flow Rate .....18 m<sup>3</sup>/hr  
Connections ..... 50 mm

### Physical Data

Length .....2,200 mm  
Width .....800 mm  
Height .....1,800 mm  
Operating Weight.....1,100 kg

## Still have a question?

Get in touch with one of our expert team today.

- ☎ 01422 371711
- ✉ [sales@newsome.ltd.uk](mailto:sales@newsome.ltd.uk)
- 🌐 [www.newsome.ltd.uk](http://www.newsome.ltd.uk)

